

ARMLIFT

FULL HYDRAULIC TELESCOPING
AERIAL LIFT

THI 36 - INSULATED AND THI 36 - STEEL



Division of TG Industries, Inc.



GENERAL SPECIFICATIONS:

- Platform Height 31'
- Working Height 36'
- Side Reach 23'
- Approx Stowed Travel Height 10'
- Rated Platform Capacity 350#
- Telescoping Boom -15 +84
- Boom Extension 10'
- Minimum Chassis Specs 15,000 GVW



STANDARD FEATURES:

- Engine Start/Stop at Bucket and Base
- Full Pressure Control Valves
- Single Stick Control at Bucket
- Extension By Hydraulic Cylinder
- Hydraulic Bucket Leveling
- Shear Ball Rotation with Enclosed Gear Box
- 720 Degree Non-Continuous Rotator
- Non-Lube Bearings
- Steel Units Only:
Fiberglass walk thru bucket with door
125 Volt Receptacle with GFI at bucket

OPTIONS:

- 180 Degree Hydraulic Bucket Rotator
- 360 Degrees Continuous Rotation
- Rear Torsion Bar
- Vinyl Bucket Cover
- 12 Volt Emergency Power at Bucket & Base
- Manual Bleed Down Valve at Bucket
- Hydraulic Tool Circuit



DIVISION OF TG INDUSTRIES, INC.
 (712) 864-3737 • Fax (712) 864-3848
 1821 HIGHWAY 15 SOUTH
 ARMSTRONG, IOWA 50514
 www.armlift.com • e-mail: tgind@ringtelco.com

ArmLift units meet or exceed all OSHA and ANSI 92.2 requirements.

NOTE: This data sheet is prepared only as a convenient source of preliminary information. Before ordering your ArmLift, contact your local dealer or the factory for complete specifications. TG Industries, Inc. reserves the right to change specifications or designs without notice.

DEALER: